



Gliptone Leathercare Ltd,
Enterprise House,
250 Halifax Road,
Todmorden,
West Yorks.
OL14 5SQ UK

Telephone +44(0)1706 819365
Fax +44(0)1706 839962
www.liquidleather.com
Company Reg. No. 05229078
Managing Director: P. B. Parkinson
Company Secretary: L. A. Parkinson

Safety data sheet in accordance with 91/155/EEC

Merithane S6

Page 1

Version : 1

Precoat

Revision Date: 20.11.2004
Date of printing : 07.02.2008

1. Identification of the substance/preparation and company

Trade name

Merithane S6 / Mericryl SX

Identification of the company

Gliptone Leathercare
Enterprise House
250 Halifax Road
Todmorden
West Yorkshire
OL14 5SQ

information about
Telephone
Emergency teleph

reparation
+642 786655

2. Composition/information on ingredients

Chemical characterization
polyurethane
in aqueous dispersion

Hazardous ingredients

N-Methyl-2-pyrrolidone	
Concentration :	2 - 6 %
CAS number :	872-50-4
Hazard symbols	Xi
R phrases	36/38

3. Hazards identification

No special hazards have to be mentioned.



Products that add life and quality, synonymous with only the finest leathers chosen by the world's most exclusive car manufacturers



Gliptone Leathercare Ltd,
Enterprise House,
250 Halifax Road,
Todmorden,
West Yorks.
OL14 5SQ UK

Telephone +44(0)1706 819365
Fax +44(0)1706 839962
www.liquidleather.com
Company Reg. No. 05229078
Managing Director: P. B. Parkinson
Company Secretary: L. A. Parkinson

Safety data sheet in accordance with 91/155/EEC

Merithane S6

Page 2

Version : 1

Revision Date: 20.11.2004
Date of printing : 07.02.2008

4. First aid measures

General information

Take affected person to fresh air.

After contact with skin

In case of contact with skin wash off immediately with plenty of water

After contact with eyes

In case of contact with eyes rinse thoroughly with water

After ingestion

Rinse mouth thoroughly with water.

Obtain medical advice.

5. Fire-fighting measures

Suitable extinguishing media

extinguishing measures to suit surroundings

Extinguishing media that must not be used for safety reasons

no restrictions

Further information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

6. Accidental release measures

Environmental precautions

Do not discharge into the subsoil/soil.

Methods for cleaning up/taking up

Take up with absorbent material

Clean equipment with water.

Additional information

Information regarding personal protective measures see, chapter 8.



Products that add life and quality, synonymous with only the finest leathers chosen by the world's most exclusive car manufacturers



Gliptone Leathercare Ltd,
Enterprise House,
250 Halifax Road,
Todmorden,
West Yorks.
OL14 5SQ UK

Telephone +44(0)1706 819365
Fax +44(0)1706 839962
www.liquidleather.com
Company Reg. No. 05229078
Managing Director: P. B. Parkinson
Company Secretary: L. A. Parkinson

Safety data sheet in accordance with 91/155/EEC

Merithane S6

Page 3

Version : 1

Revision Date: 20.11.2004
Date of printing : 07.02.2008

7. Handling and storage

Advice on safe handling
Observe the usual precautions for handling chemicals

Advice on protection against fire and explosion
No special measures necessary

8. Exposure controls/personal protection

Hygiene measures
Wash hands before breaks and after work.

Respiratory protection :	If ventilation insufficient, use a respiratory protection apparatus
Hand protection :	Protective gloves
Eye protection :	safety glasses
Body protection :	protective clothing



Products that add life and quality, synonymous with only the finest leathers chosen by the world's most exclusive car manufacturers



Gliptone Leathercare Ltd,
Enterprise House,
250 Halifax Road,
Todmorden,
West Yorks.
OL14 5SQ UK

Telephone +44(0)1706 819365
Fax +44(0)1706 839962
www.liquidleather.com
Company Reg. No. 05229078
Managing Director: P. B. Parkinson
Company Secretary: L. A. Parkinson

Safety data sheet in accordance with 91/155/EEC

Merithane S6

Page 4

Version : 1

Revision Date: 20.11.2004
Date of printing : 07.02.2008

9. Physical and chemical properties

Form :	Liquid
Colour :	milky
Odour :	characteristic
Boiling point :	100 °C
Flash point :	> 100 °C
Density :	approx. 1,0 g/cm ³
Solubility in water :	miscible
pH value :	7,5 - 9,5
Viscosity (dynamic) :	100 - 1.000 mPa.s

10. Stability and reactivity

Thermal decomposition :
No decomposition if used as prescribed.

Hazardous decomposition products
When used and handled as intended, none.

11. Toxicological information

Acute oral toxicity :	LD50 > 2.000 mg/kg (rat)
Irritant effect on skin :	non-irritant
Irritant effect on eyes :	non-irritant

Remarks

The product was classified on the basis of the calculation procedure of the preparations directive (88/379/EC).



Products that add life and quality, synonymous with only the finest leathers chosen by the world's most exclusive car manufacturers



Gliptone Leathercare Ltd,
Enterprise House,
250 Halifax Road,
Todmorden,
West Yorks.
OL14 5SQ UK

Telephone +44(0)1706 819365
Fax +44(0)1706 839962
www.liquidleather.com
Company Reg. No. 05229078
Managing Director: P. B. Parkinson
Company Secretary: L. A. Parkinson

Safety data sheet in accordance with 91/155/EEC

Merithane S6

Page 5

Version : 1

Revision Date: 20.11.2004
Date of printing : 07.02.2008

12. Ecological information

Remarks

No data available.



Products that add life and quality, synonymous with only the finest leathers chosen by the world's most exclusive car manufacturers